

## Detrex® FCC 50™ 22°

22° Baume Food Chemical Codex Grade 50ppb Trace Metal Hydrochloric Acid  
CAS No. 7647-01-0

<u>FCC Parameter</u>	<u>Specification*</u>	<u>Detrex Typical</u>
Assay	34.21 – 36.21%	35.21%
Degrees Baume	22°	22°
Specific Gravity	1.1741 – 1.1846	1.1789
Identification	Passes Test	Passes test
Iron	NMT 5 mg/kg	< 0.05 mg/kg
Lead	NMT 1 mg/kg	< 0.0001 mg/kg
Mercury	NMT 0.10 mg/kg	< 0.0001 mg/kg
Oxidizing Substances (as Cl <sub>2</sub> )	NMT 0.003%	< 0.0001%
Reducing Substances (as SO <sub>3</sub> )	NMT 0.007%	< 0.000025%
Sulfate	NMT 0.5%	< 0.00003%
Total Non-Fluorine Containing Organic Compounds	NMT 5 mg/kg including NMT 0.05 mg/kg benzene	< 0.001 mg/kg
Total Fluorinated Organic Compounds	NMT 0.0025%	< 0.0000001%
Color (APHA)	10 APHA	< 10 APHA
Nonvolatile Residue	NMT 0.5%	< 0.1 %

\* Meets Food Chemicals Codex 9<sup>th</sup> Edition Specifications.

\*All analytical testing is performed in accordance with the monograph requirements or with validated alternative test methods.

<u>Trace Metal Element</u>	<u>Specification</u>	<u>Detrex Typical*</u>
Aluminum (Al)	50 ppb max	< 25 ppb
Antimony (Sb)	50 ppb max	< 25 ppb
Arsenic (As)	50 ppb max	< 25 ppb
Barium (Ba)	50 ppb max	< 25 ppb
Beryllium (Be)	50 ppb max	< 25 ppb
Bismuth (Bi)	50 ppb max	< 25 ppb
Boron (B)	50 ppb max	< 25 ppb
Cadmium (Cd)	50 ppb max	< 25 ppb
Calcium (Ca)	50 ppb max	< 25 ppb
Chromium (Cr)	50 ppb max	< 25 ppb
Cobalt (Co)	50 ppb max	< 25 ppb
Copper (Cu)	50 ppb max	< 25 ppb
Gallium (Ga)	50 ppb max	< 25 ppb
Germanium (Ge)	50 ppb max	< 25 ppb
Gold (Au)	50 ppb max	< 25 ppb
Indium (In)	50 ppb max	< 25 ppb
Iron (Fe)	50 ppb max	< 25 ppb
Lead (Pb)	50 ppb max	< 25 ppb
Lithium (Li)	50 ppb max	< 25 ppb
Magnesium (Mg)	50 ppb max	< 25 ppb
Manganese (Mn)	50 ppb max	< 25 ppb
Molybdenum (Mo)	50 ppb max	< 25 ppb
Nickel (Ni)	50 ppb max	< 25 ppb
Niobium (Nb)	50 ppb max	< 25 ppb
Platinum (Pt)	50 ppb max	< 25 ppb
Potassium (K)	50 ppb max	< 25 ppb



## Specification Sheet FCC 50™

Silicon (Si)	50 ppb max	< 25 ppb
Silver (Ag)	50 ppb max	< 25 ppb
Sodium (Na)	50 ppb max	< 25 ppb
Strontium (Sr)	50 ppb max	< 25 ppb
Tantalum (Ta)	50 ppb max	< 25 ppb
Thallium (Tl)	50 ppb max	< 25 ppb
Thorium (Th)	50 ppb max	< 25 ppb
Tin (Sn)	50 ppb max	< 25 ppb
Titanium (Ti)	50 ppb max	< 25 ppb
Vanadium (V)	50 ppb max	< 25 ppb
Zinc (Zn)	50 ppb max	< 25 ppb
Zirconium (Zr)	50 ppb max	< 25 ppb

\*All testing completed with PerkinElmer ICP/MS